BRAKE/STANDARD VALUE

PARKING BRAKE

PARKING BRAKE

EN01E09ZZZ010701533001

STANDARD VALUE, LIMIT AND ACTION

Unit: Notch

Inspection item	Usable limit	Action
Reserve travel for parking brake lever [Operating force 245 N {25 kgf, 55 lbf}]	6-10	Adjustment

PARKING BRAKE CABLE NO.2

EN01E09ZZZ010701533002

TIGHTENING TORQUE

REGULAR CAB / TRANSMISSION M/T

Unit: N·m {kgf·cm, lbf·ft}

Tightening part		Tightening torque	Remarks
Parking brake cable assembly mounting nut		19.5 {199, 14}	_
Control cable bracket, control cable insulator, mounting nut for parking brake cable No.2	Transmission control clamp bolt of IFS model	37 {377, 27}	_
Mounting bolt for parking brake cable assembly No.2	Other than IFS model transmission control clamp bolt	19.5 {199, 14}	_
Mounting nut for parking brake cable assembly No.2		19.5 {199, 14}	_
Mounting nut for floor shift transmission control shift cable		12 {122, 8.9}	_

REGULAR CAB/TRANSMISSION A/T

Unit: N·m {kgf·cm, lbf·ft}

Tightening part	Tightening torque	Remarks
Control cable bracket, control cable insulator, mounting nut for parking brake cable No.2	19.5 {199, 14}	
Parking brake cable mounting nut	19.5 {199, 14}	_
Mounting bolt for parking brake cable No.2	19.5 {199, 14}	_

WIDE CAB/TRANSMISSION M/T

Unit: N·m {kgf·cm, lbf·ft}

Tightening part	Tightening torque	Remarks
Control cable bracket, control cable insulator, mounting nut for parking brake cable No.2	19.5 {199, 14}	_
Parking brake cable mounting nut	19.5 {199, 14}	_
Mounting bolt for parking brake cable No.2	19.5 {199, 14}	_

WIDE CAB/TRANSMISSION A/T

Unit: N·m {kgf·cm, lbf·ft}

Tightening part	Tightening torque	Remarks
Control cable bracket, control cable insulator, mounting nut for parking brake cable No.2	19.5 {199, 14}	
Parking brake cable mounting nut	19.5 {199, 14}	_
Mounting bolt for parking brake cable No.2	19.5 {199, 14}	_

Copyright(C) Hino Motors, Ltd. All rights reserved

9-17

9-18 BRAKE/STANDARD VALUE

PARKING BRAKE CABLE NO.3

EN01E09ZZZ010701533003

TIGHTENING TORQUE

PARKING DRUM INNER DIAMETER, 177.8 mm (7.000 in.)

Unit: N·m {kgf·cm, lbf·ft		
Tightening torque	Remarks	
13 {132, 9.6}	_	
95 {969, 70}	_	

Tightening part	Tightening torque	Remarks
Mounting bolt for parking brake cable No.3	13 {132, 9.6}	_
Parking brake plate mounting bolt	95 {969, 70}	_
Parking brake cable mounting nut	19.5 {199, 14}	_

PARKING DRUM INNER DIAMETER, 190 mm (7.480 in.)

Unit: N⋅m {kgf⋅cm, lbf⋅ft}

Tightening part	Tightening torque	Remarks
Parking brake cable mounting nut	19.5 {199, 14}	_
Mounting blot for parking brake cable No.3	19.5 {199, 14}	_

PARKING DRUM INNER DIAMETER, 200 mm (7.874 in.)

Unit: N⋅m {kgf⋅cm, lbf⋅ft}

Tightening part	Tightening torque	Remarks
Parking brake cable mounting nut	19.5 {199, 14}	_
Mounting blot for parking brake cable No.3	8.0 {82, 5.9}	_

PARKING DRUM INNER DIAMETER, 203.2 mm (8.000 in.)

Unit: N·m {kgf·cm, lbf·ft}

Tightening part	Tightening torque	Remarks
Mounting blot for parking brake cable No.3	19.5 {199, 14}	_
Mounting bolt for parking brake cable support bracket No.3	48 {489, 35}	_
Lock nut	19.5 {199, 14}	_
Mounting blot for parking brake cable No.3	19.5 {199, 14}	_
Parking brake cable mounting nut	19.5 {199, 14}	_

BRAKE/STANDARD VALUE

9-19

PARKING BRAKE LEVER

EN01E09ZZZ010701533004

TIGHTENING TORQUE

Unit: N·m {kgf·cm, lbf·ft}

Tightening part	Tightening torque	Remarks
Parking brake lever mounting bolt	19.5 {199, 14}	_

PARKING BRAKE DRUM

EN01E09ZZZ010701533005

STANDARD VALUE, LIMIT AND ACTION

PARKING DRUM INNER DIAMETER, 177.8 mm (7.000 in.)

Unit: mm {in.}

Inspection item	Usable limit	In the case of a new product	Action
Inner diameter of brake drum	178.8 {7.039}	177.8 {7.000}	Replace
Thickness of drum brake shoe lining	1.5 {0.059}	3.6 {0.142}	Replace

PARKING DRUM INNER DIAMETER: 190 mm (7.480 in.)

Unit: mm {in.}

Inspection item	Usable limit	In the case of a new product	Action
Inner diameter of brake drum	191 {7.520}	190 {7.480}	Replace
Thickness of drum brake shoe lining	1.0 {0.039}	4.0 {0.157}	Replace

PARKING DRUM INNER DIAMETER, 200 mm (7.874 in.)

Unit: mm {in.}

Inspection item	Usable limit	In the case of a new product	Action
Inner diameter of brake drum	201 {7.913}	200 {7.874}	Replace
Thickness of drum brake shoe lining	1.5 {0.059}	3.8 {0.150}	Replace

PARKING DRUM INNER DIAMETER, 203.2 mm (8.000 in.)

Unit: mm {in.}

Inspection item	Usable limit	In the case of a new product	Action
Inner diameter of brake drum	204 {8.031}	203.2 {8.000}	Replace
Thickness of drum brake shoe lining	1.0 {0.039}	3.75 {0.148}	Replace

9–20 BRAKE/STANDARD VALUE

TIGHTENING TORQUE

PARKING DRUM INNER DIAMETER, 177.8 mm (7.000 in.)

Unit: N⋅m {kgf⋅cm, lbf⋅ft}

Tightening par	t	Tightening torque	Remarks
Parking brake drum mounting output	Transmission M/T	127 {1,295, 94}	_
shaft rear set nut	Transmission A/T	190 {1,937, 140}	_

PARKING DRUM INNER DIAMETER: 190 mm (7.480 in.)

Unit: N⋅m {kgf⋅cm, lbf⋅ft}

Tightening part	Tightening torque	Remarks
Parking brake cable mounting nut	8.2 {84, 6.0}	_

PARKING DRUM INNER DIAMETER, 200 mm (7.874 in.)

Unit: N·m {kgf·cm, lbf·ft}

Tightening part		Tightening torque	Remarks
Mounting bolt for parking brake shoe guide plate		18 {184, 13}	_
Parking brake drum mounting output shaft rear set nut	Transmission M/T	127 {1,295, 94}	_
	Transmission A/T	190 {1,937, 140}	_

PARKING DRUM INNER DIAMETER, 203.2 mm (8.000 in.)

Unit: N·m {kgf·cm, lbf·ft}

Tightening part	Tightening torque	Remarks
Parking brake support mounting bolt (transmission side)	155 {1,581, 114}	_
Parking brake support mounting bolt (transfer side)	37-49 {378-499, 28-36}	_
Lock pin nut (transfer side)	12.7-21.6 {130-220, 10-15}	_
Mounting bolt for parking brake cable support bracket No.3	48 {489, 35}	_
Lock nut	19.5 {199, 14}	_
Mounting blot for parking brake cable No.3	19.5 {199, 14}	_
Parking brake dust cover mounting bolt	20 {204, 15}	_

PARKING BRAKE SWITCH

EN01E09ZZZ010701533006

TIGHTENING TORQUE

PARKING DRUM INNER DIAMETER: 190 mm (7.480 in.)

Unit: N·m {kgf·cm, lbf·ft}

Tightening part	Tightening torque	Remarks
Parking brake switch mounting screw	1.5 {15.3, 1.1}	_
Parking brake switch mounting screw	0.4-0.7 {4.1-7.1, 0.3-0.5}	_
Parking brake lever mounting bolt	19.5 {199, 14}	_
Output shaft lock nut	289 {2,950, 213}	_

Copyright(C) Hino Motors, Ltd. All rights reserved