300 SERIES

615 AMT 3430 WIDE HYBRID

*Overseas model pictured.
May contain items not standard to the NZ model.

Euro 6
Emissions Standard

4 x 2 Cab Chassis

KEY FEATURES

✓ Vehicle Stability Control (VSC) – incl. ABS & TC	✓ Euro 6 Emission Standard
✓ Pre-Collision System (PCS)	✓ SRS Airbag System (Driver & Passenger)
✓ Lane Departure Warning System (LDWS)	✓ Reverse Camera
✓ Cruise Control	✓ Hybrid System equipped with Idle Stop

KEY SPECIFICATIONS

GVM	5,500kg
GCM	9,000kg
Power	150hp / 110kW
Torque	470Nm
Transmission	6 Speed AMT
Wheelbase	3.4m

ENGINE

Model	HINO N04C-WR
Max. Output (ISO NET)	150hp / 110kW @ 2,700 RPM
Max. Torque (ISO NET)	470Nm @ 1,200 RPM
Max. Engine RPM	3,100 RPM
Engine Compliance	ADR 80/04 using Euro 6 Standard
Type	Diesel, turbocharged and intercooled, 4 cylinder, overhead valve, water-cooled
Combustion System	Direct injection with EGR
Bore & Stroke	104 x 118mm
Piston Displacement	4.009L
Compression Ratio	18.0:1
Fuel Injection	Electronic control common rail
Air Cleaner & Intake	Dry paper element
Exhaust	Horizontal outlet RHS
Emission Control System	DPR & SCR (AdBlue®) after treatments
Engine Immobiliser	Equipped

PERFORMANCE

Calculations based on 5,500kg GVM with 195/85R16 tyres	
Engine RPM @ 100km/h	2,133
Max. Theoretical Speed (km/h)	140
Gradeability Tan (%) @ GVM	60

BRAKES

Type	Ventilated disc front and rear	
Control	Dual-circuit hydraulic, vacuum assist	
Disc Diameter x Pad Effective Area	Front	296mm x 78.4mm²
	Rear	281mm x 72.4mm²
Air Dryer	Equipped	
Vehicle Stability Control (VSC)	Equipped	
Pre-Collision System (PCS)	Equipped	
Anti-Lock Brake System (ABS)	Equipped	
Traction Control (TC)	Equipped	
Park Brake	Mechanical, internal expanding acting on transmission output shaft, non-folding lever	
Exhaust Brake	Equipped	
Easy Start Hill Assist (ES)	Equipped	

CLUTCH

Type	Dry single plate with damper springs and auto adjuster
Facing Diameter	300mm
Control	Electronic with transmission

STEERING

Type	Telescopic tilt steering column, recirculating ball, integral power steering	
Steering Angles	Inside – 51°	Outside – 36°

POWER & TORQUE CHART (ISO NET) N04C-WR



TRANSMISSION & GEAR RATIOS

Make & Description		Hino RE62, Automated Manual 6 Speed
Type		Automated Manual 6 Speed with Overdrive
Gear Ratios	1	6.370
	2	3.870
	3	2.148
	4	1.461
	5	1.000
	6	0.703
	Reverse	5.926
Rear Axle Ratio		4.100

ELECTRICAL

Type	24V negative earth
Batteries	2 x 12V 60Ah 55D23L
Alternator Capacity	80A supplied from Hybrid system
Headlamps	LED
Electric Air Horn	Equipped
Reverse Buzzer	Equipped
Hybrid System Type	Diesel-Electric Hybrid
Motor	AC Synchronous Motor 35kW
Battery	Nickel-Metal Hydride Battery, 201V 6.5Ah

HYBRID DRIVE SYSTEM

Hybrid System Type	Diesel-Electric Hybrid
Motor Type	AC Synchronous Motor 35kW
Rated Voltage	201V
Max Output	35kW @ 1,600 RPM
Battery Type	Nickel-Metal Hydride
Battery Capacity	6.5Ah
Idle Stop	Equipped

SAFETY FEATURES

Active Safety Features	
Vehicle Stability Control (VSC)	Equipped
Anti-Lock Brake System (ABS)	Equipped
Pre-Collision System (PCS)	Equipped
PCS is inclusive of	Safety Eye (SE) Autonomous Emergency Braking (AEB) Pedestrian Detection (PD)
Traction Control (TC)	Equipped
Lane Departure Warning System (LDWS)	Equipped
Reverse Camera (RC)	Equipped
Reverse Buzzer	Equipped
Easy Start Hill Assist (ES)	Equipped
Passive Safety Features	
SRS Airbag	Equipped (for driver and passenger)
SRS Seat Belt Pretensioner	Equipped (for driver and passenger)
Front Underrun Protection Device (FUPD)	Equipped
ECE-R29 Cab Strength Certified	Equipped

AXLE, SUSPENSION & LOAD LIMITS

Front	Front Axle Type	Independent Front Suspension (IFS)
	Front Suspension Type	Double wishbone, independent coil springs with double acting shock absorbers
	Axle Limit (incl. Suspension)	2,600kg
	Tyre Limit	2,360kg
Rear	Rear Axle Model	SH12
	Rear Axle Type	Fully floating, single reduction by hypoid gears
	Rear Suspension Type	Taper leaf main and auxiliary with shock absobers and stabiliser
	Axle Limit (incl. Suspension)	4,400kg
	Tyre Limit	4,400kg

CHASSIS FRAME

Main Section (depth x flange x thickness)	190.8 x 65 x 4.9mm
Chassis Width	750mm
Tensile Strength	540 N/mm² (55 kgf/mm²)
Tow Hook (Front & Rear)	Equipped
Type	Ladder-shaped channel section side rails

FUEL TANK & SUPPLY

Material	Steel
Fuel Capacity	80L
Lockable Fuel Cap	Equipped
Prefilter & Sedimenter	Equipped
AdBlue® Capacity	13L

CAB DETAILS

Type	Forward control, all steel construction with torsion bar tilt mechanism, fully trimmed
Grille Colour	White
Seating Capacity	3
Driver's Seat	4-way adjustable, urethane foam pads
Side Passenger Seat	Fixed bench, split back, urethane foam pads
Seat Covering	Fabric type
Seat Belts	3-point lap sash for driver and side passenger, 2-point lap for centre position
Sunvisor & Overhead Console	Equipped (for driver and side passenger)
Windscreen Wipers	2-arm wiper and washers, 2-speed with intermittent
Cab Heater & Air Conditioner	Equipped with 4-speed fan
Auxiliary Power Supply	24V socket
Rear-View Mirrors	**Internal:** Single centre mounted flat type **External:** Aspherical type, long stay, 2 convex spotters
Floor Covering	Vinyl type
Central Locking & Keyless Entry	Equipped with immobiliser
Cab Storage Pockets	Equipped in driver's seat back pocket
Centre Fold Down Tray	Equipped
Power Windows	Equipped
Foot Rest	Equipped
Multimedia System	10.1" UXGA capacity touch screen, wireless Apple CarPlay and Android Auto compatible, AM/FM+RDS/ DAB+radio, Bluetooth 5.0 phone & audio, input for up to 6 cameras, USB 2.0 and 3.0, 2.4GHz Wi-Fi enabled

INSTRUMENTATION

LCD Display	Steering Wheel & Column Controls
✓ Date, Day, & Time	✓ Cruise Control
✓ Temperature Gauge	✓ MID Controls
✓ Fuel & AdBlue® Gauges	✓ Headlights & Indicators
✓ Odometer & Hour Meter	✓ Window Wiper Controls
Multi Information Display (MID)	**Additional Switches & Controls**
✓ General Information	✓ External Flat Mirror Control
✓ Cruise Control	✓ VSC, PCS, & LDWS Off
✓ Eco Tree	✓ Idle Up & Quick Warm Up
✓ Display Setting	✓ Mirror Heater
✓ Safe Driving Settings	✓ Engine Brake
✓ System Check	✓ DPR Regeneration
Meters & Gauges	✓ Headlight Leveller
✓ Speedometer	✓ Hazard Lights
✓ Tachometer	✓ ES Start Control

WHEELS & TYRES

Wheel Type	5-stud disc wheel (JIS type) PCD 203.2mm
Rim Size	16" x 5.5"
Tyre Size	195/85R16 111/109
Number of Tyres	7 incl. spare
Spare Tyre Carrier	Equipped

DIMENSIONS (MM)	
Model	XKU710R-WKVMVQ3
Product Code	615 AMT 3430 WIDE HYBRID MY26
Suspension	Leaf
Wheelbase (WB)	3,430
Overall Length (OL)	6,135
Cab Width (CW)	1,995
Overall Width (OW) – at rear tyres	1,905
Overall Height (OH)	2,200
Cab to Axle Centre (CA)	2,870
Front Overhang (FOH)	1,125
Rear Overhang (ROH)	1,580
Front Chassis Height (FCH)	675
Rear Chassis Height (RCH)	745
Front Track (FT)	1,665
Rear Track (RT)	1,480
Road Clearance (RC)	170
Kerb to Kerb	11,800
Wall to Wall	13,200
Indicative Chassis Mass (kg) – with 10L of fuel, standard tools, spare tyre, and subject to a ±3% tolerance	
Total	2,550
Front	1,730
Rear	820
GVM	5,500
GCM	9,000

CHASSIS DRAWINGS (PLEASE REFER TO DIMENSIONS TABLE ABOVE)







Drawings are for reference only to the table. For specific chassis layouts and dimensions, please refer to Body Mounting Manual drawings.

WARRANTY (PLEASE REFER TO HDL WARRANTY CONDITIONS)	
Standard Warranty	Engine & Powerlines
36 months or 100,000kms (whichever comes first)	

DISCLAIMER

Hino Trucks are distributed in New Zealand by Hino Distributors (NZ) Ltd.

All efforts have been made to ensure the information contained in this brochure was correct at time of printing or uploading. Hino Distributors (NZ) Ltd reserves the right to alter any details of the specifications and equipment without notice. Hino in so far as it is permitted by law to do so, shall not be liable in any way as a result of any reliance placed by any person on anything contained in this brochure. You should therefore check with your authorised Hino dealer at the time of ordering your motor vehicle to ensure that colour, specifications, equipment, design features and options are available for the vehicle you are ordering. Please note that some options may only be available in combination with others. Authorised Hino dealers will on request provide up to date information on all accessories, design features, prices and availability.